HELICOPTER HOIST AREA INSPECTION

CERTIFICATE

SENVION 6.2M 126

OWF NORDERGRÜNDE

The helicopter hoist areas on stated wind turbine generators and located in mentioned offshore wind farm have been inspected according to legal national regulations (SOLF) and, where applicable, to other national standards for offshore installations. The hoist areas have been found suitable for helicopter hoist operations subject to below stated limitations, non-compliances and authorization by the approving authority.

HELICOPTER HOIST AREA INFORMATION

HEIGHT HHA	CENTRE HHA – ROTOR WTG	MAX. LOAD CAPACITY
280 ft MSL	13.73 m	4238 kg

LIMITATIONS

HHO FROM SUNRISE TO SUNSET ONLY
MAX. WIND SPEED FOR HHO: 18 m/s
MAX. WIND SPEED FOR EVACUATION HHO - 23 m/s

NON-COMPLIANCES

NIL

NEXT DUE

31.12.2027

27.04.2026
Inspection date

DIN EN ISO/IEC 17024 EUROPEAN CERTIFIED Cert-Nr: 1-14-1012 Steffen Bechtel CERTIFICATION CYF 2007

Inspected by

The operator of the hoist area is fully responsible to ensure that the hoist area and the related equipment are fit for purpose according to legal regulations.
This certificate will cease to be valid if changes to the hoist area or the related equipment are being made without prior agreement with *windpark heliflight consulting GmbH.*