

HELICOPTER HOIST AREA INSPECTION

CERTIFICATE

SIEMENS SWT-4.0-120

OWF BORKUM RIFFGRUND 01

The helicopter hoist areas on stated wind turbine generators and located in mentioned offshore wind farm have been inspected according to legal national regulations (Gemeinsame Grundsätze des Bundes und der Länder über Windenbetriebsflächen auf Windenergieanlagen & BSH Standard Konstruktive Ausführung von Offshore-Windenergieanlagen) and, where applicable, to other national standards for offshore helidecks (CAP 437). The hoist areas have been found suitable for helicopter hoist operations subject to below stated limitations, non-compliances and authorization by the approving authority.

HELICOPTER HOIST AREA INFORMATION

HEIGHT HHA	CENTRE HHA – ROTOR WTG	MAX. LOAD CAPACITY
302 ft MSL	10.148 m	1300 kg

LIMITATIONS

HHO FROM SUNRISE TO SUNSET ONLY
MAX. WIND SPEED FOR HHO: 22 m/s
MAX. WIND SPEED FOR EVACUATION HHO - 23 m/s

NON-COMPLIANCES

FOR NON-COMPLIANCES SEE HELICOPTER HOIST AREA MANUAL

NEXT DUE

31.12.2019

12.02.2019

Inspection date



Inspected by