

HELICOPTER HOIST AREA INSPECTION

CERTIFICATE

MHI V164 – 8.3

OWF BORKUM RIFFGRUND 02

The helicopter hoist areas on stated wind turbine generators and located in mentioned offshore wind farm have been inspected according to legal national regulations (Gemeinsame Grundsätze des Bundes und der Länder über Windenbetriebsflächen auf Windenergieanlagen & BSH Standard Konstruktive Ausführung von Offshore-Windenergieanlagen) and, where applicable, to other national standards for offshore helidecks (CAP 437). The hoist areas have been found suitable for helicopter hoist operations subject to below stated limitations, non-compliances and authorization by the approving authority.

HELICOPTER HOIST AREA INFORMATION

HEIGHT HHA	CENTRE HHA – ROTOR WTG	MAX. LOAD CAPACITY
385 ft MSL	10.33 m	2800 kg

LIMITATIONS

HHO FROM SUNRISE TO SUNSET ONLY
MAX. WIND SPEED FOR HHO: 22 m/s
MAX. WIND SPEED FOR EVACUATION HHO - 23 m/s
MAX. HELICOPTER DOWNWASH: 982 N/m ²

NON-COMPLIANCES

RAILING HEIGHT EXCEEDS LEGAL STIPULATIONS (TOTAL HEIGHT 2.00 m)
FOR NON-COMPLIANCES SEE HELICOPTER HOIST AREA MANUAL

NEXT DUE

31.12.2019

13.02.2019

Inspection date



Hartmann

Inspected by