

HELICOPTER HOIST AREA INSPECTION

# CERTIFICATE

## SWT-3.6-120

OWF RIFFGAT

The helicopter hoist areas on stated wind turbine generators and located in mentioned offshore wind farm have been inspected according to legal national regulations (Gemeinsame Grundsätze des Bundes und der Länder über Windenbetriebsflächen auf Windenergieanlagen & BSH Standard Konstruktive Ausführung von Offshore-Windenergieanlagen) and, where applicable, to other national standards for offshore helidecks (CAP 437). The hoist areas have been found suitable for helicopter hoist operations subject to below stated limitations, non-compliances and authorization by the approving authority.

### HELICOPTER HOIST AREA INFORMATION

HEIGHT HHA	CENTRE HHA – ROTOR WTG	MAX. LOAD CAPACITY
305 ft MSL	10.26 m	1300 kg / 375 kg/m <sup>2</sup>

### LIMITATIONS

HHO FROM SUNRISE TO SUNSET ONLY
MAX. HELICOPTER DOWNWASH: 25 m/s
MAX. WIND SPEED FOR HHO: 23 m/s
MAX. WIND SPEED FOR EVACUATION HHO - 24 m/s

### NON-COMPLIANCES


FOR NON-COMPLIANCES SEE HELICOPTER HOIST AREA MANUAL
--

### NEXT DUE

31.12.2020
------------

19.03.2019  
Inspection date



  
Inspected by