

HELICOPTER HOIST AREA INSPECTION

CERTIFICATE

AREVA M5000

OWF GLOBAL TECH 1

The helicopter hoist areas on stated wind turbine generators and located in mentioned offshore wind farm have been inspected according to legal national regulations (Gemeinsame Grundsätze des Bundes und der Länder über Windenbetriebsflächen auf Windenergieanlagen & BSH Standard Konstruktive Ausführung von Offshore-Windenergieanlagen) and, where applicable, to other national standards for offshore helidecks (CAP 437). The hoist areas have been found suitable for helicopter hoist operations subject to below stated limitations, non-compliances and authorization by the approving authority.

HELICOPTER HOIST AREA INFORMATION

HEIGHT HHA	CENTRE HHA – ROTOR WTG	MAX. LOAD CAPACITY
311 ft MSL	10.40 m	500 kg

LIMITATIONS

HHO FROM BEGINNING OF MORNING CIVIL TWILIGHT TO END OF EVENING CIVIL TWILIGHT ONLY
MAX. WIND SPEED FOR HHO: 25 m/s

NON-COMPLIANCES


FOR NON-COMPLIANCES SEE HELICOPTER HOIST AREA MANUAL

NEXT DUE

31.12.2020

19.02.2019

Inspection date



Inspected by