

GLOBAL TECH I

HLD IDENTIFICATION

GT I

ICAO IDENTIFIER

EHHI

OSS SIDE IDENTIFICATION

GT I

FIXED PERMANENTLY MANNED INSTALLATION
GLOBAL TECH I OFFSHORE WIND GMBH

HLD REFERENCE POINT			
N 54° 30.81'		E 006° 22.11'	
LANGEN INFORMATION 128.525 MHz	AMSTERDAM INFORMATION 119.175 MHz		GT I RADIO ROOM / HLO 151.110 MHz
WEATHER INFORMATION 131.635 MHz 7x		LIGHTING & DIMMING 131.635 MHz 3x 100% 4x 30% (10%) 5x 10% (3%)	
HELIDECK HEIGHT 149 ft MSL	D-VALUE 20 m		MTOW 11 t
APPROACH / DEPARTURE CORRIDOR 090° / 270° DECK HEADING 360°			
HIGHEST OBSTACLE ON INSTALLATION 15 ft ABOVE HLD (ANTENNA MAST)		HIGHEST OBSTACLE IN THE VICINITY 495 ft MSL (WTG)	
REFUELLING FACILITY JET-A1 (GRAVITY)	GROUND POWER UNIT YES	LANDING NET N/A	STATUS LIGHT N/A
FIRE FIGHTING FACILITIES			
2x MONITOR MAN ACTIVATION	2x HYDRANT FLEXIBLE HOSES (25 m)	2x 10 kg CO2	2x 25 kg DRY POWDER



GLOBAL TECH I

HLD IDENTIFICATION
GT I

ICAO IDENTIFIER
EHHI

OSS SIDE IDENTIFICATION
GT I

FIXED PERMANENTLY MANNED INSTALLATION
GLOBAL TECH I OFFSHORE WIND GMBH

HLD REFERENCE POINT			
N 54° 30.81'		E 006° 22.11'	
LANGEN INFORMATION 128.525 MHz	AMSTERDAM INFORMATION 119.175 MHz		GT I RADIO ROOM / HLO 151.110 MHz
WEATHER INFORMATION 131.635 MHz 7x		LIGHTING & DIMMING 131.635 MHz 3x 100% 4x 30% (10%) 5x 10% (3%)	
HELIDECK HEIGHT 149 ft MSL	D-VALUE 20 m		MTOW 11 t
APPROACH / DEPARTURE CORRIDOR 090° / 270° DECK HEADING 360°			
HIGHEST OBSTACLE ON INSTALLATION 15 ft ABOVE HLD (ANTENNA MAST)		HIGHEST OBSTACLE IN THE VICINITY 495 ft MSL (WTG)	
REFUELLING FACILITY JET-A1 (GRAVITY)	GROUND POWER UNIT YES	LANDING NET N/A	STATUS LIGHT N/A
FIRE FIGHTING FACILITIES			
2x MONITOR MAN ACTIVATION	2x HYDRANT FLEXIBLE HOSES (25 m)	2x 10 kg CO2	2x 25 kg DRY POWDER
NON - COMPLIANCES • NIL		LIMITATIONS • NIL	
REMARKS • CONTACT GT RADIO ROOM / HLO PRIOR TO ENTERING OWF AND FOR FURTHER CLEARANCES • BE AWARE OF WTG IN CLOSE PROXIMITY TO HELIDECK • PPR FOR REFUELLING (JET-A1)			

GLOBAL TECH I

HLD IDENTIFICATION

GT I

ICAO IDENTIFIER

EHHI


OSS SIDE IDENTIFICATION

GT I

FIXED PERMANENTLY MANNED INSTALLATION
GLOBAL TECH I OFFSHORE WIND GMBH

HLD REFERENCE POINT			
N 54° 30.81'		E 006° 22.11'	
LANGEN INFORMATION 128.525 MHz	AMSTERDAM INFORMATION 119.175 MHz	GT I RADIO ROOM / HLO 151.110 MHz	
WEATHER INFORMATION 131.635 MHz 7x		LIGHTING & DIMMING 131.635 MHz 3x 100% 4x 30% (10%) 5x 10% (3%)	
HELIDECK HEIGHT 149 ft MSL	D-VALUE 20 m	MTOW 11 t	
APPROACH / DEPARTURE CORRIDOR 090° / 270° DECK HEADING 360°			
HIGHEST OBSTACLE ON INSTALLATION 15 ft ABOVE HLD (ANTENNA MAST)		HIGHEST OBSTACLE IN THE VICINITY 495 ft MSL (WTG)	
REFUELLING FACILITY JET-A1 (GRAVITY)	GROUND POWER UNIT YES	LANDING NET N/A	STATUS LIGHT N/A
FIRE FIGHTING FACILITIES			
2x MONITOR MAN ACTIVATION	2x HYDRANT FLEXIBLE HOSES (25 m)	2x 10 kg CO2	2x 25 kg DRY POWDER

INSTALLATION PROFILE VIEW (NORTH)



OSS SIDE IDENTIFICATION

GT I

HLD REFERENCE POINT

E 006° 22.11'

INSTALLATION TOP VIEW

OFS

360°

090° / 270°

090° / 270°

255°

105°

LOS

N

p.5

GLOBAL TECH I

DEPARTURE GTI EE

HLD IDENTIFICATION
GT I

ICAO IDENTIFIER
EHHI

OSS SIDE IDENTIFICATION
GT I

EXIT POINT GTIEE

N 54° 30.81'

E 006° 25.25'

DEPARTURE DIRECTION
090°

DEPARTURE PROCEDURE

- DEPART ON TRACK 090°
- OBSTACLE-FREE WHEN WITHIN DEPARTURE CORRIDOR
- ABOVE WTG HEIGHT WHEN PASSING 495 ft MSL
- CORRIDOR DESIGNED TO REACH 200 ft ABOVE WTG HEIGHT AT EXIT POINT GTIEE (4.5% CLIMB RATE)

DEPARTURE TOP VIEW



EXIT
GTIEE

695 ft*

2.0 NM

090°

*200 ft above WTG

GLOBAL TECH I

DEPARTURE GTI EW

HLD IDENTIFICATION
GT I

ICAO IDENTIFIER
EHHI

OSS SIDE IDENTIFICATION
GT I

EXIT POINT GTIEW

N 54° 30.81'


E 006° 18.67'

DEPARTURE DIRECTION
270°

DEPARTURE PROCEDURE

- DEPART ON TRACK 270°
- OBSTACLE-FREE WHEN WITHIN DEPARTURE CORRIDOR
- ABOVE WTG HEIGHT WHEN PASSING 495 ft MSL
- CORRIDOR DESIGNED TO REACH 200 ft ABOVE WTG HEIGHT AT EXIT POINT GTIEW (4.5% CLIMB RATE)

DEPARTURE TOP VIEW



*200 ft above WTG