

WINDLIFT 1

HLD IDENTIFICATION
WINDLIFT 1

VESSEL SIDE IDENTIFICATION
WINDLIFT 1

JACK-UP VESSEL
WINDLIFT 1

BRIDGE / HLO

CONTACT FREQUENCY TBD WITH PROJECT

WEATHER INFORMATION ON REQUEST		LIGHTING & DIMMING ON REQUEST	
HELIDECK HEIGHT VARIABLE	D-VALUE 19,50 m	MTOW 9.3 t	
HELIDECK POSITION ON VESSEL BOW			
HIGHEST OBSTACLE ON VESSEL CRANE (VARIABLE) 4x LEGS (VARIABLE)			
REFUELLING FACILITY N/A	GROUND POWER UNIT N/A	LANDING NET YES	
TD/PM LIGHTING N/A	HELIPORT IDENT LIGHTING N/A	STATUS LIGHT N/A	
FIRE FIGHTING FACILITIES			
2 MONITOR MANUAL ACTIVATION	2 HYDRANTS 2x FLEXIBLE HOSES	CO₂ 2x 18 kg	DRY POWDER 2x 25 kg



WINDLIFT 1

 HLD IDENTIFICATION
WINDLIFT 1

 VESSEL SIDE IDENTIFICATION
WINDLIFT 1

 JACK-UP VESSEL
 WINDLIFT 1

BRIDGE / HLO			
CONTACT FREQUENCY TBD WITH PROJECT			
WEATHER INFORMATION ON REQUEST		LIGHTING & DIMMING ON REQUEST	
HELIDECK HEIGHT VARIABLE	D-VALUE 19,50 m	MTOW 9.3 t	
HELIDECK POSITION ON VESSEL BOW			
HIGHEST OBSTACLE ON VESSEL CRANE (VARIABLE) 4x LEGS (VARIABLE)			
REFUELLING FACILITY N/A	GROUND POWER UNIT N/A	LANDING NET YES	
TD/PM LIGHTING N/A	HELIPORT IDENT LIGHTING N/A	STATUS LIGHT N/A	
FIRE FIGHTING FACILITIES			
2 MONITOR MANUAL ACTIVATION	2 HYDRANTS 2x FLEXIBLE HOSES	CO₂ 2x 18 kg	DRY POWDER 2x 25 kg
NON – COMPLIANCES <ul style="list-style-type: none"> • ACCESS STARBOARD INFRINGES 180° OFS • RADAR MAST STARBOARD INFRINGES 210° OFS 		LIMITATIONS <ul style="list-style-type: none"> • CRANE BOOM MUST BE OUT OF REST POSITION FOR ALL HELICOPTER OPERATIONS TO ENSURE LOS CLEARANCE 	
REMARKS <ul style="list-style-type: none"> • CONTACT BRIDGE / HLO FOR CLEARANCES, REQUESTS AND INFORMATION • HELIDECK ORIENTATION TO BE TAKEN FROM HLD STATUS REPORT • HELIDECK HEIGHT TO BE CHECKED FOR EACH LOCATION • OVERFLIGHT OF VESSEL PROHIBITED 			

WINDLIFT 1

HLD IDENTIFICATION
WINDLIFT 1

VESSEL SIDE IDENTIFICATION
WINDLIFT 1

JACK-UP VESSEL
WINDLIFT 1

BRIDGE / HLO			
CONTACT FREQUENCY TBD WITH PROJECT			
WEATHER INFORMATION ON REQUEST		LIGHTING & DIMMING ON REQUEST	
HELIDECK HEIGHT VARIABLE	D-VALUE 19,50 m	MTOW 9.3 t	
HELIDECK POSITION ON VESSEL BOW			
HIGHEST OBSTACLE ON VESSEL CRANE (VARIABLE) 4x LEGS (VARIABLE)			
REFUELLING FACILITY N/A	GROUND POWER UNIT N/A	LANDING NET YES	
TD/PM LIGHTING N/A	HELIPORT IDENT LIGHTING N/A	STATUS LIGHT N/A	
FIRE FIGHTING FACILITIES			
2 MONITOR MANUAL ACTIVATION	2 HYDRANTS 2x FLEXIBLE HOSES	CO₂ 2x 18 kg	DRY POWDER 2x 25 kg
VESSEL PROFILE VIEW (STARBOARD)			

WINDLIFT 1

HLD IDENTIFICATION
WINDLIFT 1

VESSEL SIDE IDENTIFICATION
WINDLIFT 1

JACK-UP VESSEL
WINDLIFT 1

BRIDGE / HLO			
CONTACT FREQUENCY TBD WITH PROJECT			
WEATHER INFORMATION ON REQUEST		LIGHTING & DIMMING ON REQUEST	
HELIDECK HEIGHT VARIABLE	D-VALUE 19,50 m	MTOW 9.3 t	
HELIDECK POSITION ON VESSEL BOW			
HIGHEST OBSTACLE ON VESSEL CRANE (VARIABLE) 4x LEGS (VARIABLE)			
REFUELLING FACILITY N/A	GROUND POWER UNIT N/A	LANDING NET YES	
TD/PM LIGHTING N/A	HELIPORT IDENT LIGHTING N/A	STATUS LIGHT N/A	
FIRE FIGHTING FACILITIES			
2 MONITOR MANUAL ACTIVATION	2 HYDRANTS 2x FLEXIBLE HOSES	CO₂ 2x 18 kg	DRY POWDER 2x 25 kg

VESSEL TOP VIEW

